

EoC MDU Wi-Fi ATA Voice Endpoint

May 2013

EoC MDU Wi-Fi ATA Voice EP With In-Building Coax

Last Meters Distribution

Providing a Managed

700Mbps / 350Mbps

High Speed Data + Voice

+ MIMO 2x2 11n Wi-Fi

Triple Play by QoS and IPv6 Support

No additional network wiring ...

The Most Powerful Coax MDU Solution with Remote Management and Auto Provision.

INTRODUCTION

THE COAX MDU VOICE ENDPOINT, CEV-750, IS THE BROADBAND ACCESS AND VOIP DEVICE OVER THE EXISTING COAXIAL CABLE WITH WI-FI EXTENSION.

NO ADDITIONAL NETWORK WIRING IS NECESSARY.

CABLE OPERATORS MAY JUST USE THE EXISTING COAX WIRING OF CABLE OPERATORS OR IN THE MDU BUILDING, THEN BE READY TO PROVIDE THE BROADBAND TRIPLE-PLAY SERVICES TO SUBSCRIBERS.

LOW INITIAL DEPLOYMENT COST. THE LOW INITIAL COST CAN EXPAND THE SERVICE TO SMALL SCALE BUILDING WITH HIGHER SPEED THAN CMTS. DUAL SUPPORT OF IPV4 AND IPV6 PROVIDE THE FLEXIBILITY FOR OPERATORS.

WITH HIGH THROUGHPUT AND QoS, IT CAN OPTIMIZE TRIPLE PLAY SERVICES.

AUTO PROVISIONING AND REMOTE MANAGEMENT. IT MINIMIZES THE INSTALLATION AND SUPPORT COST. THE UNIQUE ENDPOINT SERVICE CONTROL SUPPORTS SERVICE PROVIDERS WITH DIFFERENT SERVICE LEVELS AND SERVICE SCHEMES.



Model : CEV -750

FEATURES

- Design for Operators Providing High Speed Data Wi-Fi and Voice Service over Coax Network
- EoC up to 700/350 Mbps PHY/Throughput Rate as Distribution Backbone over Coax
- Up to 70dB Attenuation on Coax Network
- Two 10/100M Fast Ethernet Ports
- Telephone FXS Port with SIP Protocol Support
- MIMO 2x2 11b/g/n Wi-Fi Access Point Support
- Ethernet Loop Detection and Isolation
- Filter Built-in to Eliminate Noise from TV
- QoS Priority/Mapping and TagVLAN Support
- Service and Bandwidth Control